

## Safety Data Sheet

# Hi-Clean Spray

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**Product Code** HCS002

**Issued Date** 2019/06/01

**Product Type/ Use** Process oil.

**Supplier Telephone Numbers**

CHANG MING TRADING CO., LTD

11F-10 · No.188, Sec.5, Nanking E. Rd.,

Taipei 105,

TAIWAN

**Emergency Tel.**

02-77072288

**Telephone/Fax Number**

Tel: 02-27697700 Fax: 02-37651659

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Preparation Description**

Highly refined mineral oils. The highly refined mineral oil contains <3% (w/w)

DMSO-extract, according to IP346.

CAS NO. 8042-47-5 100%

### 3. HAZARDS IDENTIFICATION

**Human Health Hazards**

No specific hazards under normal use conditions. Prolonged or repeated exposure may cause dermatitis.

Used oil may contain harmful impurities.

**Safety Hazards**

Not classified as flammable, but will burn.

**Environmental Hazards**

Not classified as dangerous for the environment.

### 4. FIRST AID MEASURES

**Symptoms and Effects**

Not expected to give rise to an acute hazard under normal conditions of use.

**Inhalation**

In the unlikely event of dizziness or nausea, remove casualty to fresh air. If symptoms persist, obtain medical attention.

#### **Skin**

Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.

#### **Eye**

Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

#### **Ingestion**

Wash out mouth with water and obtain medical attention. Do not induce vomiting.

#### **Advice to Doctor**

Treat symptomatically. Aspiration into the lungs may result in chemical pneumonitis. Dermatitis may result from prolonged or repeated exposure. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.

## **5. FIRE FIGHTING MEASURES**

### **Specific Hazards**

Combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide and unidentified organic and inorganic compounds.

### **Extinguishing Media**

Foam and dry chemical powder. Carbon dioxide, sand or earth may be used for small fires only.

### **Unsuitable Extinguishing Media**

Water in jet. Use of halon extinguishers should be avoided for environmental reasons.

### **Protective Equipment**

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions**

Avoid contact with skin and eyes. Wear PVC, Neoprene or nitrile rubber gloves. Wear rubber knee length safety boots and PVC Jacket and Trousers. Wear safety glasses or full face shield if splashes are likely to occur.

### **Environmental Precautions**

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Inform local authorities if this cannot be prevented.

### **Clean-up Methods - Small Spillages**

Absorb liquid with sand or earth. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

### **Clean-up Methods - Large Spillages**

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

## **7. HANDLING AND STORAGE**

### **Handling**

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Avoid prolonged or repeated contact with skin. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Cloth, paper and other materials that are used to absorb spills present a fire hazard. Avoid their accumulation by disposing of them safely and immediately. In addition to any specific recommendations given for controls of risks to health, safety and the environment, an assessment of risks must be made to help determine controls appropriate to local circumstances.

### **Storage**

Keep in a cool, dry, well-ventilated place. Use properly labelled and closeable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

### **Storage Temperatures**

0°C Minimum. 50°C Maximum.

### **Recommended Materials**

For containers or container linings, use mild steel or high density polyethylene.

### **Unsuitable Materials**

For containers or container linings, avoid PVC.

### **Other Information**

Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

## **8. EXPOSURE CONTROLS, PERSONAL PROTECTION**

### **Exposure Limits**

#### **Substance Regulations Exposure Duration**

#### **Exposure Limit Units Notes**

Oil mist, mineral PEL 1997 TWA 5 mg/m<sup>3</sup>

PEL 1997 STEL 10 mg/m<sup>3</sup>

PEL 1997 Factories (Permissible Exposure Levels of Toxic Substances) Order (S 343/96), January 1997

#### **Exposure Controls**

Use local exhaust ventilation if there is a risk of inhalation of vapours, mists or aerosols.

#### **Respiratory Protection**

Not normally required. If oil mist cannot be controlled, a respirator fitted with an organic vapour cartridge combined with a particulate pre-filter should be used.

#### **Hand Protection**

PVC or nitrile rubber gloves.

#### **Eye Protection**

Wear safety glasses or full face shield if splashes are likely to occur.

#### **Body Protection**

Minimise all forms of skin contact. Overalls and shoes with oil resistant soles should be worn. Launder overalls and undergarments regularly.

#### **Environmental Exposure Controls**

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Colour** Clear, Colourless.

**Physical State** Liquid at ambient temperature.

**Odour** Odourless.

**pH Value** Not applicable.

**Vapour Pressure** Expected to be less than 0.5 Pa at 20°C.

**Initial Boiling Point** Expected to be above 280°C.

**Solubility in Water** Negligible.

**Density** 850 kg/m<sup>3</sup> at 15°C.

**Flash Point** 180°C (COC).

**Flammable Limits - Upper** 10% V/V (typical) (based on mineral oil).

**Flammable Limits - Lower** 1% V/V (typical) (based on mineral oil).

**Auto-Ignition Temperature** Expected to be above 320°C.

**Kinematic Viscosity** 15 mm<sup>2</sup>/s at 40°C.

**Evaporation Rate** Data not available.

**Vapour Density (Air=1)** Greater than 1.

**Partition co-efficient, n-octanol/water** Log Pow expected to be greater than 6.

## **10. STABILITY AND REACTIVITY**

**Pour Point** -12°C.

### **Stability**

Stable.

### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

### **Materials to Avoid**

Strong oxidizing agents.

## **11. TOXICOLOGICAL INFORMATION**

### **Hazardous Decomposition Products**

Hazardous decomposition products are not expected to form during normal storage.

### **Basis for Assessment**

Toxicological data have not been determined specifically for this product.

Information given is based on a knowledge of the components and the toxicology of similar products.

### **Acute Toxicity - Oral**

LD50 expected to be > 2000 mg/kg.

### **Acute Toxicity - Dermal**

LD50 expected to be > 2000 mg/kg.

### **Acute Toxicity - Inhalation**

Not considered to be an inhalation hazard under normal conditions of use.

### **Eye Irritation**

Expected to be slightly irritating.

### **Skin Irritation**

Expected to be slightly irritating.

### **Respiratory Irritation**

If mists are inhaled, slight irritation of the respiratory tract may occur.

### **Skin Sensitisation**

Not expected to be a skin sensitizer.

### **Carcinogenicity**

Product is based on mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.

### **Mutagenicity**

Not considered to be a mutagenic hazard.

### **Reproductive Toxicity**

Not considered to be toxic to reproduction.

### **Other Information**

Prolonged and/or repeated contact with this product can result in defatting of the skin,

particularly at elevated temperatures. This can lead to irritation and possibly dermatitis, especially under conditions of poor personal hygiene. Skin contact should be minimised. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed. Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

## **12. ECOLOGICAL INFORMATION**

### **Basis for Assessment**

Ecotoxicological data have not been determined specifically for this product.

Information given is based on a knowledge of the components and the ecotoxicology of similar products.

### **Mobility**

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

### **Persistence / Degradability**

Not expected to be readily biodegradable. Expected to be inherently biodegradable.

### **Bioaccumulation**

Has the potential to bioaccumulate.

### **Ecotoxicity**

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Product is expected to be practically non-toxic to aquatic organisms, LL/EL50 >100 mg/l. (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

### **Other Adverse Effects**

Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities.

## **13. DISPOSAL CONSIDERATIONS**

### **Waste Disposal**

Recycle or dispose of in accordance with prevailing regulations, by a recognized collector or contractor. The competence of the contractor to deal satisfactorily with this type of product should be established beforehand.

Do not pollute the soil, water or environment with the waste product.

### **Product Disposal**

As for waste disposal.

#### **Container Disposal**

Recycle or dispose of in accordance with the legislation in force with a recognized collector or contractor.

### **14. TRANSPORT INFORMATION**

#### **Transport Information**

Not dangerous for transport under UN, IMO, and IATA/ICAO codes.

### **15. REGULATORY INFORMATION**

EC Symbols None.

EC Risk Phrase Not classified.

EC Safety Phrase Not classified.

EINECS All components listed or polymer exempt.

#### **National Legislation**

Singapore Guidelines on Preparation of MSDS.

Environmental Pollution Control (Hazardous Substance)

Factories Act 1973.

#### **Packaging & Labelling**

Safety data sheet available for professional user on request.

### **16. OTHER INFORMATION**

#### **Restrictions**

This product must not be used in applications other than recommended without first seeking the advice of the  
CHANG MING technical department.

#### **Technical Contact Numbers**

27697700

#### **Further Information**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It does not constitute a guarantee for any specific property of the product.

**... End Of SDS ...**